

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-323015

(43)Date of publication of application : 26.11.1999

(51)Int.Cl.

C08K 9/10

C08K 5/523

C08L101/00

D06M 13/282

D06M 15/667

(21)Application number : 11-073528

(71)Applicant : TORAY IND INC

(22)Date of filing : 18.03.1999

(72)Inventor : TAKEDA MASANOBU
SEKI MASAO

(30)Priority


Priority number : 10 70291 Priority date : 19.03.1998 Priority country : JP

(54) FLAME-RETARDANT RESIN COMPOSITION AND FLAME-RETARDANT FIBER STRUCTURE

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain the subject composition having excellent flame retardancy, resin film formability and resin film strength, scarcely bleeding a flame retardant on the surface and not generating a poisonous substance containing a halogen on combustion by compounding a flame retardant encapsulated in microcapsules and a thermoplastic resin.

SOLUTION: This flame-retardant resin composition comprises (A) a flame retardant {preferably a flame retardant not containing a halogen, more preferably a phosphorous compound, especially a flame-retardant compound of the formula [R1 to R4 are each phenyl, cresyl or xylenyl; (n) is 1-20]} encapsulated in microcapsules and (B) a thermoplastic resin (a polyolefinic resin, a polyester-based resin, a polyurethane-based resin, etc.,). The microcapsules are added in a temperature



B/temperature A ratio of preferably 100 pts.wt./(10-200 pts.wt.), more preferably 100 pts.wt./ (20-80 pts.wt.).

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]